



## ARKÉ: C-USB supply unit 60W PD Metal

**19298.60.M**

Wiring devices / Traditional wiring devices / ARKÉ / Devices

### C-USB supply unit 60W PD Metal

#### Product Status

3 - Active

#### Minimum order quantity

10 NR



#### Sheets, Manuals, Documentation

- [Light Multilanguage instructions sheet \(502 kb\)](#)
- [Full Multilanguage instructions sheet \(964 kb\)](#)

## Drawings

## Technical data

- **Class group:** Domestic switching devices
- **Class:** USB power supply
- **Model:** Bus
- **Number of ports USB-A:** 0
- **Number of ports USB-C:** 1
- **Operating voltage:** 120,00 - 240,00 V
- **Frequency:** 50,00 - 60,00 HZ
- **Max. output current:** 3.000 mA
- **Output voltage:** 5,00 - 20,00 V
- **Connection type:** Screwed terminal
- **Mounting method:** Flush-mounted
- **Colour:** Aluminium
- **Device width:** 44,80 mm
- **Device height:** 49,00 mm
- **Device depth:** 42,30 mm
- **Suitable for degree of protection (IP):** IP20
- **Impact strength:** Other
- **Anti-bacterial treatment:** No

## Certifications

- 00. CE Marking - EU
- 01. IMQ - Italy
- 37. Marking - Morocco
- 44. USB-IF mark
- 99. WEEE Directive ([download](#))

# Packaging



**Code** 8007352738157  
**Quantity** 1 NR  
**Dim.** 6x5.4x5.2 [cm]  
**Weight** 77.2 [g]



**Code** 8007352738164  
**Quantity** 10 NR  
**Dim.** 28.1x13.1x6 [cm]  
**Weight** 847.6 [g]



**Code** 8007352753907  
**Quantity** 120 NR  
**Dim.** 38.5x29x30 [cm]  
**Weight** 10,651.2 [g]

# Legal

Vimar reserves the right to change at any time and without notice the characteristics of the products reported. Installation should be carried out by qualified staff in compliance with the current regulations regarding the installation of electrical equipment in the country where the products are installed. For the terms of use of the information on the product info sheet see [Conditions of Use](#).