



30012.C

Wiring devices / Traditional wiring devices / LINEA / Devices

1P 10AX reversing switch in-line canvas

1P 10 AX 250 V~ lightable aligned reversing switch, replaceable button, canvas. Max 100 W for lamps with built-in power supply unit (IEC 60669-1:2017)

Product Status

3 - Active

Minimum order quantity

50 NR

You may also be interested in



30004.C - 1P 10AX 2-way

switch in-line canvas



30008.C - 1P NO 10A button 00943.W - Linea 110-250V canvas white LED unit

Drawings





Technical data

- Class group: Domestic switching devices
- Class: Installation switch
- Wiring system: Intermediate switch
- Method of operation: Rocker/button
- Assembly arrangement: Modular device for domestic switching devices
- Number of modules (module system): 1
- Push button switch: Yes
- Number of rockers: 1
- Mounting method: Flush-mounted
- Type of fastening: Engage (snap)
- With mounting plate: No
- Material: Plastic
- Material quality: Thermoplastic
- Halogen free: Yes
- Anti-bacterial treatment: No
- Surface protection: Untreated
- Surface finishing: Matt
- **Colour**: Beige
- RAL-number (similar): 7032
- Label space/information surface: No

Certifications

- 00. CE Marking EU
- 01. IMQ Italy (download)
- 13. SNI Indonesia

Packaging



 Code
 8007352690455

 Quantity
 1 NR

 Dim.
 4.6x2.7x5.6 [cm]

 Weight
 33.8 [g]

Code 800 **Quantity** 50 N

Dim.

Weight

8007352690462 **y** 50 NR 23.7x14.8x12.8 [cm] 1,873 [g]



 Code
 8007352690479

 Quantity
 300 NR

 Dim.
 45.5x27x27 [cm]

 Weight
 11,662 [g]

Legal

Vimar reserves the right to change at any time and without notice the characteristics of the products reported.Installation should be carried out by qualified staff in compliance with the current regulations regarding the installation of electrical equipment in the country where the products are installed.For the terms of use of the information on the product info sheet see Conditions of Use.

- Illumination: Optional
- **Function lighting**: Control and orientation
- Type of lighting: LED exchangeable
- Suitable for degree of protection (IP): IP40
- Impact strength: Other
- Nominal voltage: 250 V
- Rated current: 10,00 A
- Switching current for fluorescent lamps: 10
- Feedback-signal contact: No
- **Connection type**: Screwed terminal
- Heating switch: No
- Washing machine switch: No
- Device width: 22,30 mm
- Device height: 52,80 mm
- Device depth: 43,85 mm
- Built-in depth: 35,50 mm
- **Compatible with Apple HomeKit**: No
- **Compatible with Google Assistant**: No
- **Compatible with Amazon Alexa**: No
- IFTTT support available: No
- 37. Marking Morocco
- 96. Electrotechnical expert (download)
- 99. WEEE Directive (download)