



## LINEA: 1P 10AX reversing switch mechanism

---

### 30012

Wiring devices / Traditional wiring devices / LINEA / Devices

### 1P 10AX reversing switch mechanism

1P 10 AX 250 V~ lightable reversing switch mechanism, to be completed with 1-module button. Max 100 W for lamps with built-in power supply unit (IEC 60669-1:2017)

### Product Status

3 - Active

### Minimum order quantity

50 NR




## You may also be interested in




31000S.B - White lower 1M path light button



31000S.G - Black lower 1M path light button



31000S.C - Lower 1M path light button Canvas




31000A.B - Axial button 1M white



31000A.G - Axial button 1M black



31000A.C - Axial button 1M canvas



31000.B - Button 1M aligned white



31000.G - Button 1M aligned 1M black



31000.C - Button 1M aligned Canvas



00943.W - Linea 110-250V white LED unit

## Drawings

## Technical data

- **Class group:** Domestic switching devices
- **Class:** Installation switch
- **Wiring system:** Intermediate switch
- **Method of operation:** Rocker/button
- **Assembly arrangement:** Modular device for domestic switching devices
- **Number of modules (module system):** 1
- **Push button switch:** Yes
- **Number of rockers:** 1
- **Mounting method:** Flush-mounted
- **Type of fastening:** Engage (snap)
- **With mounting plate:** No
- **Material:** Plastic
- **Material quality:** Thermoplastic
- **Halogen free:** Yes
- **Anti-bacterial treatment:** No
- **Surface protection:** Untreated
- **Surface finishing:** Matt
- **Colour:** Black
- **RAL-number (similar):** 7024
- **Label space/information surface:** No
- **Illumination:** Optional
- **Function lighting:** Control and orientation
- **Type of lighting:** LED exchangeable
- **Suitable for degree of protection (IP):** IP40
- **Nominal voltage:** 250 V
- **Rated current:** 10,00 A
- **Switching current for fluorescent lamps:** 10
- **Feedback-signal contact:** No
- **Connection type:** Screwed terminal
- **Heating switch:** No
- **Washing machine switch:** No
- **Device width:** 22,30 mm
- **Device height:** 49,50 mm
- **Device depth:** 39,20 mm
- **Built-in depth:** 35,50 mm
- **Compatible with Apple HomeKit:** No
- **Compatible with Google Assistant:** No
- **Compatible with Amazon Alexa:** No
- **IFTTT support available:** No

## Certifications

- 00. CE Marking - EU
- 01. IMQ - Italy ([download](#))
- 13. SNI - Indonesia
- 37. Marking - Morocco
- 96. Electrotechnical expert ([download](#))
- 99. WEEE Directive ([download](#))

## Packaging



**Code** 8007352674493  
**Quantity** 1 NR  
**Dim.** 4.6x2.7x5.6 [cm]  
**Weight** 33.8 [g]



**Code** 8007352674509  
**Quantity** 50 NR  
**Dim.** 23.7x14.8x12.8 [cm]  
**Weight** 1,873 [g]



**Code** 8007352674516  
**Quantity** 300 NR  
**Dim.** 45.5x27x27 [cm]  
**Weight** 11,662 [g]

## Legal

Vimar reserves the right to change at any time and without notice the characteristics of the products reported. Installation should be carried out by qualified staff in compliance with the current regulations regarding the installation of electrical equipment in the country where the products are installed. For the terms of use of the information on the product info sheet see [Conditions of Use](#).