



LINEA: Stand alone universal dimmer 230V black

30135.G

Wiring devices / Traditional wiring devices / LINEA / Devices

Stand alone universal dimmer 230V black

Universal 230 V~ 50 Hz phase cutting dimmer, for 40-400 W incandescent lamps, 40-300 VA electronic transformers, 10-200 W CFL lamps, 3-200 W LED lamps, for LED phase cutting electronic power supply units, ON/OFF control and adjustment with built-in push buttons or via NO peripheral push buttons, minimum brightness control, visible in darkness, black



Product Status

3 - Active

Minimum order quantity

1 NR

Sheets, Manuals, Documentation

- [Light Multilanguage instructions sheet \(1390 kb\)](#)
- [Full Multilanguage instructions sheet \(1559 kb\)](#)

Drawings


Technical data

- **Class group:** Domestic switching devices
- **Class:** Dimmer
- **Assembly arrangement:** Modular device for domestic switching devices
- **Method of operation:** Push button
- **Number of modules (module system):** 1
- **App control via Bluetooth:** No
- **Dimming phase cut-on:** Yes
- **Dimming phase cut-off:** Yes
- **Serial dimmer:** Yes
- **Type of load:** Universal and LED Retrofit
- **Substation input:** Yes
- **Light value memory:** Yes
- **Applicable with button:** Yes
- **Applicable with movement sensor:** No
- **Applicable with presence indicator:** No
- **Applicable with time switch/timer:** No
- **Applicable with transmission button:** No
- **Applicable with infrared button:** No
- **Mounting method:** Flush-mounted
- **Type of fastening:** Snapper mounting
- **Material:** Plastic
- **Material quality:** Thermoplastic
- **Halogen free:** Yes
- **Surface protection:** Untreated
- **Surface finishing:** Matt
- **Colour:** Black
- **RAL-number (similar):** 7021
- **Transparent:** No
- **Suitable for degree of protection (IP):** IP40
- **Nominal voltage:** 230,00 - 230,01 V
- **Frequency:** 50,00 - 50,01 HZ
- **Control voltage:** 230,00 - 230,01 V
- **Nominal power resistive load:** 40 - 400 W
- **Nominal power inductive load:** 40 - 300 VA
- **Nominal power capacitive load:** 40 - 300 VA
- **Max. switching power LED:** 200 W
- **Connection type:** Screwed terminal
- **Core cross section:** 0,00 - 250,00
- **Device width:** 22,20 mm
- **Device height:** 52,70 mm
- **Device depth:** 48,70 mm
- **Compatible with Apple HomeKit:** No
- **Compatible with Google Assistant:** No
- **Compatible with Amazon Alexa:** No
- **IFTTT support available:** No

Certifications

- 00. CE Marking - EU
- 01. IMQ - Italy ([download](#))
- 37. Marking - Morocco
- 37. Marking - Morocco
- 99. WEEE Directive ([download](#))

Packaging



Code 8007352713703
Quantity 1 NR
Dim. 6x4.5x5.4 [cm]
Weight 48.78 [g]



Code 8007352713710
Quantity 10 NR
Dim. 23.5x12.5x6.5 [cm]
Weight 487.8 [g]

Legal

Vimar reserves the right to change at any time and without notice the characteristics of the products reported. Installation should be carried out by qualified staff in compliance with the current regulations regarding the installation of electrical equipment in the country where the products are installed. For the terms of use of the information on the product info sheet see [Conditions of Use](#).