



LINEA: IoT connected RFID reader canvas

30812.C

Wiring devices / View Wireless wiring devices / LINEA / Devices

IoT connected RFID reader canvas

RFID smart card landing reader, card configuration using VIEW Wireless App, Bluetooth technology standard, IoT technology on Bluetooth technology 5.0 standard for the creation of VIEW Wireless mesh system, 1 relay output NO 16 A 100-240 V~, 1 DND input, LED with brightness control, 100-240 V~ 50/60 Hz power supply, canvas - 2 modules

Product Status

3 - Active

Minimum order quantity

1 NR



Sheets, Manuals, Documentation

- [Light Multilanguage instructions sheet \(780 kb\)](#)
- [Full Multilanguage instructions sheet \(1333 kb\)](#)
- [Manuel appli View Wireless \(37703 kb\)](#)
- [Manual app View Wireless \(37528 kb\)](#)
- [Manual View Wireless app \(37579 kb\)](#)
- [Εγχειρίδιο τεχνικού εγκατάστασης \(37781 kb\)](#)
- [Installationsanleitung View Wireless \(37508 kb\)](#)
- [Manuale installatore Portale View Vimar \(3245 kb\)](#)
- [Manuel Portail View Vimar \(2101 kb\)](#)
- [Manual Portal Vimar View \(2069 kb\)](#)
- [Vimar View Portal installer manual \(2173 kb\)](#)
- [Εγχειρίδιο χρήσης Πύλη View Vimar \(2210 kb\)](#)
- [Bedienungsanleitung Portal View Vimar \(2182 kb\)](#)
- [Manuale app View Wireless \(15836 kb\)](#)

Drawings

Technical data

- **Class group:** Alarm installations, emergency call and signalling
- **Class:** Access control system
- **Standalone:** No
- **Networkable:** Yes
- **PC-binding:** No
- **Type of interface:** Other
- **Reading strategy:** Code
- **Signalling:** Light signal
- **Mounting method:** Flush-mounted
- **Operating voltage AC 50 Hz:** 100,00 - 240,00 V
- **Operating voltage AC 60 Hz:** 100,00 - 240,00 V
- **Operating temperature:** 5 - 45 °C
- **Degree of protection (IP):** IP20
- **Colour:** Other
- **Model:** Reader
- **Material:** Plastic
- **Power over Ethernet (PoE):** None
- **Width:** 44,80 mm
- **Height:** 52,80 mm
- **Depth:** 40,30 mm
- **Compatible with Apple HomeKit:** No
- **Compatible with Google Assistant:** No
- **Compatible with Amazon Alexa:** No
- **VdS class:** None

Certifications

- 00. CE Marking - EU ([download](#))
- 37. Marking - Morocco
- 46. UK PSTI compliance ([download](#))
- 99. WEEE Directive ([download](#))

Packaging



Code 8007352689671
Quantity 1 NR
Dim. 6x5.4x5.2 [cm]
Weight 71 [g]

Code 8007352689688
Quantity 10 NR
Dim. 28.1x13.1x6 [cm]
Weight 797.4 [g]

Code 8007352689695
Quantity 120 NR
Dim. 38.5x29x30 [cm]
Weight 10,010 [g]

Legal

Vimar reserves the right to change at any time and without notice the characteristics of the products reported. Installation should be carried out by qualified staff in compliance with the current regulations regarding the installation of electrical equipment in the country where the products are installed. For the terms of use of the information on the product info sheet see [Conditions of Use](#).